




General Description

Silicon VDMOS and LDMOS transistors designed specifically for broadband RF applications. Suitable for Military Radios, Cellular and Paging Amplifier Base Stations, Broadcast FM/AM, MRI, Laser Driver and others.

"Polyfet"™ process features gold metal for greatly extended lifetime. Low output capacitance and high F_t enhance broadband performance



PATENTED GOLD METALIZED SILICON GATE ENHANCEMENT MODE RF POWER VDMOS TRANSISTOR

200 Watts Gemini

Package Style AR

HIGH EFFICIENCY, LINEAR, HIGH GAIN, LOW NOISE

ABSOLUTE MAXIMUM RATINGS (TC = 25 °C)

| Total Device Dissipation | Junction to Case Thermal Resistance | Maximum Junction Temperature | Storage Temperature | DC Drain Current | Drain to Gate Voltage | Drain to Source Voltage | Gate to Source Voltage |
|--------------------------|-------------------------------------|------------------------------|---------------------|------------------|-----------------------|-------------------------|------------------------|
| 440 Watts | 0.4 °C/W | 200 °C | -65 °C to 150 °C | 20 A | 70 V | 70V | 30V |

RF CHARACTERISTICS (200 WATTS OUTPUT)


| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|--------|--------------------------|-----|-----|------|----------|--|
| Gps | Common Source Power Gain | 10 | | | dB | $I_{dq} = 2 A, V_{ds} = 28.0 V, F = 175 MHz$ |
| n | Drain Efficiency | | 55 | | % | $I_{dq} = 2 A, V_{ds} = 28.0 V, F = 175 MHz$ |
| VSWR | Load Mismatch Tolerance | | | 20:1 | Relative | $I_{dq} = 2 A, V_{ds} = 28.0 V, F = 175 MHz$ |

ELECTRICAL CHARACTERISTICS (EACH SIDE)


| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|--------|------------------------------------|-----|------|-----|-------|---|
| Bvdss | Drain Breakdown Voltage | 65 | | | V | $I_{ds} = 0.25 A, V_{gs} = 0V$ |
| Idss | Zero Bias Drain Current | | | 5 | mA | $V_{ds} = 28.0 V, V_{gs} = 0V$ |
| Igss | Gate Leakage Current | | | 1 | uA | $V_{ds} = 0 V, V_{gs} = 30V$ |
| Vgs | Gate Bias for Drain Current | 1 | | 7 | V | $I_{ds} = 0.5 A, V_{gs} = V_{ds}$ |
| gM | Forward Transconductance | | 5 | | Mho | $V_{ds} = 10V, V_{gs} = 5V$ |
| Rdson | Saturation Resistance | | 0.18 | | Ohm | $V_{gs} = 20V, I_{ds} = 20 A$ |
| Idsat | Saturation Current | | 30 | | Amp | $V_{gs} = 20V, V_{ds} = 10V$ |
| Ciss | Common Source Input Capacitance | | 200 | | pF | $V_{ds} = 28.0 V, V_{as} = 0V, F = 1 MHz$ |
| Crss | Common Source Feedback Capacitance | | 25 | | pF | $V_{ds} = 28.0 V, V_{as} = 0V, F = 1 MHz$ |
| Coss | Common Source Output Capacitance | | 150 | | pF | $V_{ds} = 28.0 V, V_{as} = 0V, F = 1 MHz$ |

F1120


POUT VS PIN GRAPH




CAPACITANCE VS VOLTAGE




IV CURVE



ID AND GM VS VGS



S11 AND S22 SMITH CHART



PACKAGE DIMENSIONS IN INCHES

